




WC009B Auto Robotic Arm Collar Band Attaching Machine





Round-tip Collar Band

It is applied on the collar band attaching process for shirt. Simple operation and low sewing skill requirements.

- One-click to generate size parameter.
- Style changing only takes 10 minutes, adjustable mechanical mold (universal).
- Robotic arm cooperates with lockstitch machine with trimmer, edge trimming automatically.
- Only require operator to place the fabric pieces, and the machine will automatically complete the subsequent sewing process.
- No need programming on the robotic arm, sewing pattern input by computer conveniently.
- Output can reach 100 pieces/hour.

APPLICATIONS

Styles

Round-tip Collar Band

Fabrications

Woven Fabric

Size and Dimensions

Collar Length: 400~600mm

Collar Band Height: 35~60mm(Clear Height)

Collar Fall and Collar Band Curve Difference Value: 0~25mm

Collarband Bottom Sagitta Difference Value: 0~10mm

Pre-process Requirements

Cutting piece should be same with the pattern, and standard interlining, with the difference less than 1mm.

qonvolv
SYSTEMS

Quaternion Hong Kong Limited
13/F, Harbour Center, 25 Harbour Road
Wanchai, Hong Kong

| www.qonvolv.com
| qonvolvSystems@qonvolv.com
| 86-757-88888070



SPECIFICATIONS



Sewing Machine Head
JUKI DLM5400NDDD7WBK /AK85B



Dimensions (mm)
L: 1,700 x W: 1,700 x H: 1,500



Stitch Type
Lockstitch (#301)



Power (W)
5,000



Compressed Air Requirement (Mpa)
0.5



Power Supply (V)
AC 220 (50Hz)



Needle
DBx1



Max. Sewing Speed (rpm)
3,000



Changeover Time (m)
**20(New pattern)
5(Historical pattern)**



Weight (kg)
350



Output (pcs/ hr)
100