





WF005A

**Auto Self-fold Under Placket
Sewing Machine**





Self-folded single fold under placket



Self-folded double fold under placket

Automatic sewing for shirt under placket.

- Simple operation, only require operator to place the panels, and the sewing process is completed automatically by machine.
- Under placket sewing and interlining attaching are completed simultaneously with automation.
- Stable quality, with a better flatness appearance comparing to the traditional operation.
- For those products with interlining, it can achieve free interlining effect at the bottom, improving the product appearance.
- Quick changeover and adaptive sewing, automatically collect completed products.
- Replacing the traditional operation with folder.

APPLICATIONS

Styles

Self-folded single fold under placket
Self-folded double fold under placket,
which can attach the interlining

Fabrications

Applicable to most regular woven fabric.
Prior testing is suggested for special fabrications.

Size and Dimensions

Length of cut piece (mm) : 500~900
Width of cut piece (mm) : 250~450

Size of seam allowance (cm) :
For self-folded single fold under placket, the allowance is 1cm
For self-folded double fold under placket, the allowance is full

Interlining width (cm) : 2~3.5

SPECIFICATIONS



Sewing Machine Head
JUKI DDL-8000A



Dimensions (mm)
L: 2,910 x W: 1,520 x H: 1,720



Stitch Type
Lockstitch (#301)



Power (W)
3,500



Compressed Air Requirement (Mpa)
0.6



Power Supply (V)
AC 220 (50Hz)



Needle
#8~18



Max. Sewing Speed (rpm)
2,500~3,000



Changeover Time (m)
5



Weight (kg)
510



Output (pcs/ hr)
135~155

qonvolv
SYSTEMS

Quaternion Hong Kong Limited
13/F, Harbour Center, 25 Harbour Road
Wanchai, Hong Kong

| www.qonvolv.com
| qonvolvSystems@qonvolv.com
| 86-757-88888070

